

Technical specifications:



Epping Forest Supreme

Product Name	:	Epping Forest Supreme	
Application	:	Lawns, roof gardens, patios, swimming pool surround etc.	
Producer	:	GrassInc. BV, Oss, the Netherlands	
Production process	:	Tufted cut pile	
Pile material	:	100% C-shape PE monofilament with PP rootzone	
Yarn Dtex	:	12.000Dtex / 16 ply	
Quality	:	100% European product, free of heavy metals and toxics.	
Primary Backing	:	100% PP, UV stabilised, approx 160 gr./m2	+/- 10%
Coating	:	SBR latex, approx 800 gr. / m2	+/- 10%
Waterpermaebility	:	> 300 ml per minute per 100 cm2	
Pile height	:	approx. 25 mm	+/- 10%
Total height of construction	:	approx. 27 mm	+/- 10%
Pile Weight	:	approx. 1060 gr./m2	+/- 10%
Total weight of construction	:	approx. 2022 gr./m2	+/- 10%
Tuftgauge	:	3/8' gauge	
Stitches per linear metre	:	130	+/- 10%
Stitches per square metre	:	13.650	+/- 10%
Filaments per square metre	:	436.800	+/- 10%
UV stability	:	20 years warranty in Northern Europe	
	:	10 years warranty in Southern Europe	
Lightfastness	:	Bluescale 1-8 > 7 (according DIN 54004)	
Colourfastness	:	Greyscale 1-5 >4 (according DIN standard)	
Roll width	:	2 metres or 4 metres	+/- 1%
Rolllength	:	target length approx. 30 linear metres	

All data above are subject to modifications based upon technical improvements or company internal developments. All figures are average values and can vary slightly.

Please contact info@nevermowuk.co.uk if you have any questions.