



## Technical specifications:

### ***New Forest Supreme***

|                              |   |  |         |
|------------------------------|---|--|---------|
| Product Name                 | : | New Forest Supreme                                       |         |
| Application                  | : | Lawns, roof gardens, patios, swimming pool surround etc. |         |
| Producer                     | : | GrassInc. BV, Oss, the Netherlands                       |         |
| Production process           | : | Tufted cut pile  |         |
| Pile material                | : | 100% PE double C-shape with PP rootzone                  |         |
| Yarn Dtex                    | : | 10.050Dtex / 14 ply                                      |         |
| Quality                      | : | 100% European product, free of heavy metals and toxics.  |         |
| Primary Backing              | : | 100% PP, UV stabilised, approx 160 gr./m2                | +/- 10% |
| Coating                      | : | SBR latex, approx 800 gr. / m2                           | +/- 10% |
| Water Permeability           | : | > 300 ml per minute per 100 cm2                          |         |
| Pile height                  | : | approx. 28 mm  | +/- 10% |
| Total height of construction | : | approx. 30 mm  | +/- 10% |
| Pile Weight                  | : | approx. 985 gr./m2                                       | +/- 10% |
| Total weight of construction | : | approx. 2010 gr./m2                                      | +/- 10% |
| Tuftgauge                    | : | 3/8' gauge   |         |
| Stitches per linear metre    | : | 130  | +/- 10% |
| Stitches per square metre    | : | 13.650   | +/- 10% |
| Filaments per square metre   | : | 382.200  | +/- 10% |
| UV stability                 | : | 10 years warranty in Northern Europe                     |         |
|                              | : | 20 years warranty in Southern Europe                     |         |
| Lightfastness                | : | Bluescale 1-8 > 7 (according DIN 54004)                  |         |
| Colourfastness               | : | Greyscale 1-5 >4 (according DIN standard)                |         |
| Roll width                   | : | 2 metres or 4 metres                                     | +/- 1%  |
| Rolllength                   | : | target length approx. 30 linear metres                   |         |

All data above are subject to modifications based upon technical improvements or company internal developments. All figures are average values and can vary slightly.

Please contact [info@nevermowuk.co.uk](mailto:info@nevermowuk.co.uk) if you have any questions.